TR3370 High Opacity White Resin

Flat Head Color

RIBBON PROPERTIES

Base Film Thickness	4.5 ± 0.4 µ
Ink Thickness	4.8 ± 0.2 µ
Total Thickness	9.3 ± 0.6 µ
Transfer Temperature	375°F / 191°C

PRINTER SUBSTRATES

- Polyesters (Gloss Topcoat)
- Polyesters (Matte Topcoat)
- PVC Shrink Wrap

CERTIFICATIONS

- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant
- UL References:
  - » **Avery Dennison:** PGJI2.MH17205
  - » **FLEXcon:** PGJI2.MH16635



PRODUCT FEATURES

Exceptional Opacity

▶ Delivers bright, opaque white prints for high visibility and contrast.

Formulated for PVC Shrink Tubing

▶ Designed specifically for optimal performance on PVC shrink tubing applications.

Scratch and Smudge Resistant

▶ Provides strong protection against scratching and smudging, ensuring clean, sharp images and text that last.

INDUSTRIES & APPLICATIONS

- Appliances & Electrical
- Food & Beverage

The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation
1001 Technology Drive | Mount Pleasant, PA 15666
1.888.569.7222 info@dnp.imgcomm.com am.dnpribbons.com