TRX-50 General Purpose Wax-Resin

Flat Head Color

RIBBON PROPERTIES

Base Film Thickness	4.5 ± 0.3 µ
Ink Thickness	3.3 ± 0.2 µ
Total Thickness	7.8 ± 0.5 µ
Transfer Temperature	185°F / 85°C

PRINTER SUBSTRATES

- Coated Face Sheets
- Coated Tag
- Gloss Sheets
- Polyethylene
- Polyolefin
- Polypropylene
- Polystyrene
- Uncoated Face Sheets
- Uncoated Tag
- Vinyl (Topcoat)

CERTIFICATIONS

- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant
- UL References:
  - » **FLEXcon:** PGJI2.MH16635



PRODUCT FEATURES

Compatible with Low-End Synthetics

▶ Specifically designed for optimal performance on low-end synthetic materials.

Remarkable Edge Definition

▶ Produces crisp, clear edges for high-quality prints.

Enhanced Durability

▶ Designed to maintain print quality even under demanding conditions.

INDUSTRIES & APPLICATIONS

- Appliances & Electrical
- Automotive
- Building & Industrial Supplies
- Fashion & Textiles
- Food & Beverage
- Horticulture
- Inventory & Logistics
- Medical & Healthcare
- Personal Care
- Pharmaceutical & Supplements

The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation
1001 Technology Drive | Mount Pleasant, PA 15666
1.888.569.7222 info@dnp.imgcomm.com am.dnpribbons.com