V390 High-Speed TTO Resin

Near Edge (TTO) Color

RIBBON PROPERTIES

Base Film Thickness	4.0 ± 0.4 µ
Ink Thickness	1.4 ± 0.5 µ
Total Thickness	5.4 ± 0.9 µ
Transfer Temperature	344°F / 173°C

PRINTER SUBSTRATES

- Gloss Sheets
- Polyesters (Gloss Topcoat)
- Polyesters (Matte Topcoat)
- Polyethylene
- Polyolefin
- Polypropylene
- Polystyrene
- Vinyl (Topcoat)

CERTIFICATIONS

- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant



PRODUCT FEATURES

Optimal for Graphic-Heavy Packaging

▶ Perfectly suited for flood coats and graphic-heavy packaging.

Scratch and Smudge Resistant

▶ Provides strong protection against scratching and smudging, ensuring clean, sharp images and text that last.

Remarkable Edge Definition

▶ Produces crisp, clear edges for high-quality prints.

INDUSTRIES & APPLICATIONS

- Food & Beverage
- Horticulture
- Medical & Healthcare
- Personal Care
- Pharmaceutical & supplements

The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation
1001 Technology Drive | Mount Pleasant, PA 15666
1.888.569.7222 info@dnp.imgcomm.com am.dnpribbons.com