V4085plus Versatile Resin-Enhanced Wax

Flat Head Color

RIBBON PROPERTIES

Base Film Thickness	4.5 ± 0.3 µ
Ink Thickness	3.2 ± 0.2 µ
Total Thickness	7.7 ± 0.5 µ
Transfer Temperature	150°F / 66°C

PRINTER SUBSTRATES

- Coated Face Sheets
- Coated Tag
- Gloss Sheets
- Polyethylene
- Polyolefin
- Polypropylene
- Uncoated Face Sheets
- Uncoated Tag
- Vinyl (Topcoat)

CERTIFICATIONS

- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant
- UL References:
  - » **FLEXcon:** PGJI2.MH16635



PRODUCT FEATURES

Versatility Series

▶ Ideal for a wide range of applications and substrates, this ribbon is designed to be Ready for Anything.

Industry Leader

▶ For over two decades, our wax has been the trusted choice for top-tier performance, consistently setting the benchmark for quality and reliability.

Quick and Uniform Melting

▶ Optimizes the printing process with its high concentration of carnauba wax.

INDUSTRIES & APPLICATIONS

- Fashion & Textiles
- Food & Beverage
- Inventory & Logistics
- Medical & Healthcare
- Personal Care
- Pharmaceutical & Supplements

The information on this datasheet was obtained in DNP laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

DNP Imagingcomm America Corporation
1001 Technology Drive | Mount Pleasant, PA 15666
1.888.569.7222 info@dnp.imgcomm.com am.dnpribbons.com