Increase Productivity & Maintain Label Integrity

LD3000

2.25"(57mm) wide — Electric Label Dispenser "HIGH SPEED"

- Ideal for small labels and small work areas
- Automatically peels labels from the liner and advances labels
- New built-in 1/4" bracket for hanging capability for use with workbenches and LDHANGER16 (Reel Holder Arm Extention PRT-019-01 required for LD3000 series)
- Will dispense labels and die-cut parts
- Photosensor accuracy and reliability
- Anodized aluminum construction
- Will dispense labels from .25" to 2.25" (6 to 57mm) in width
- Will dispense labels from .25" to 3" (6 to 76mm) in length
- Works with most clear material



HANGING BRACKET



Patented



LD3000FDA

USDA/FDA Compliant Coating and CFIA Approved

- USDA/FDA compliant coating ideal for food and pharmaceutical industries
- Proprietary coating available for all label dispensers
- Call us at 972.248.1999 or email info@startinternational.com for additional info



LD3500ESD

Electrostatic Dissipative Electric Label Dispenser

- Electrostatic discharge safe
- Used for highly sensitive electronics and is certified to meet electronic industry standards



LD3500

For Clear Materials

- Dispenses Clear, Tamper Evident, Carton Sealing Labels and other challenging clear materials
- Vertical strip plate provides improved photosensor adjustability for detection of clear materials

Additional Info for **LD3000, LD3000ESD, LD3000FDA and LD3500**

- Will accommodate core sizes of 1" (25mm) and 3" (76mm)
- Automatically rewinds liner scrap for a cleaner working environment
- Liner scrap is easily removed
- No tools required for adjusting to different size labels
- No maintenance required
- **Made in the U.S.A.**



Suggested accessory:
LDPBATTERY
Rechargeable External Battery Pack

See Accessories Page 31

MODEL #	Liner Capacity Width	Length	Roll Capacity	Feed Speed*	Dimensions	Electrical Requirements	Weight
LD3000 LD3000ESD LD3000FDA	.25" to 2.25" (6mm to 57mm)	.25" to 3" (6mm to 76mm)	7.5" (19.1cm)	2.2"/sec* (5.6cm/sec.)	7.0"(L) x 6.1"(W) x 10.7"(H) 17.8cm(L) x 15.5cm(W) x 27.2cm(H)	12V DC with Universal transformer, 100V - 240V AC CE	2.8 lbs (1.27 kg)
LD3500	.25" to 2.25" (6mm to 57mm)	.25" to 4" (6mm to 102mm)	7.5" (19.1cm)	2.2"/sec* (5.6cm/sec.)	7.0"(L) x 6.1"(W) x 10.7"(H) 17.8cm(L) x 15.5cm(W) x 27.2cm(H)	12V DC with Universal transformer, 100V - 240V AC CE	2.8 lbs (1.27 kg)

*Feed Speed calculated at take-up hub origin. Feed Speed will increase as material dispenses. Speed calculated at 60Hz.