Electric

Additional info for **LD6050**

- Will dispense labels and die-cut parts
- Adjustable strip plate for hard-to-release labels
- Will accommodate core sizes of 1" (25 mm) and 3" (76mm)
- Automatically rewinds liner scrap for a cleaner working environment
- Liner scrap is easily removed
- No tools required for adjusting to different size labels
- No maintenance required

Additional info for **LD6025**

- Will dispense labels and die-cut parts
- Adjustable strip plate for hard-to-release labels
- Will accommodate core sizes of 1" (25 mm) and 3" (76mm)
- Can dispense paper, polyester, vinyl, acetate, foam, foil, etc.
- Automatically rewinds liner scrap for a cleaner working environment
- Liner scrap is easily removed
- No tools required for adjusting to different size labels
- No maintenance required
- All 230V machines are CE Certified

SPECIAL APPLICATIONS

- For clear labels and materials, please select Model # LD6050C or LD6025C

Suggested accessory:
LDHANGER16
16" (40.6cm) wide



See Accessories Page 31

For 230V machines, please add "-2" to the end of the model number. (Example: LD6050-2)

LD6050

4.75" (121mm) wide — Electric Label Dispenser "HIGH SPEED"



- Ideal for virtually any kind of label from bar code to packaging
- Automatically peels and advances labels
- Built-in 1/4" bracket for hanging capability for use with workbenches and LDHANGER16
- Photosensor accuracy and reliability
- Anodized aluminum construction
- High-torque motor for heavy rolls of labels
- Will dispense labels from .25" to 4.75" (6 to 121mm) in width
- Will dispense labels from .50" to 6" (13 to 152mm) in length
- Made in U.S.A.

COMMON MATERIALS



HANGING BRACKET



Patented

LD6050FDA

USDA/FDA Compliant Coating and CFIA Approved



- USDA/FDA compliant coating ideal for food and pharmaceutical industries

LD6025

4.75" (121mm) wide — Electric Label Dispenser



- Ideal for short length and tiny bar code labels
- Automatically peels and advances labels
- Built-in 1/4" bracket for hanging capability for use with workbenches and LDHANGER16
- Photosensor accuracy and reliability
- Anodized aluminum construction
- High-torque motor for heavy rolls of labels
- Will dispense labels from .25" to 4.75" (6 to 121mm) in width
- Will dispense labels from .125" to 6" (3 to 152mm) in length
- Made in U.S.A.

COMMON MATERIALS



HANGING BRACKET



Patented

MODEL #	Liner Capacity Width	Length	Roll Capacity	Feed Speed*	Dimensions	Electrical Requirements	Weight
LD6025	.25" to 4.75" (6mm to 121mm)	.125" to 6" (3mm to 152mm)	12" (31cm)	1.6"/sec* (3.9cm/sec.)	10.8"(L) x 10.8"(W) x 14.5"(H) 27.4cm(L) x 27.4cm(W) x 36.8cm(H)	100/115V AC, 0.75A 60Hz (220-240V AC, 0.4A 50Hz CE)	7.0 lbs (3.18 kg)
LD6050	.25" to 4.75" (6mm to 121mm)	.50" to 6" (13mm to 152mm)	12" (31cm)	3.3"/sec* (8cm/sec.)	10.8"(L) x 10.8"(W) x 14.5"(H) 27.4cm(L) x 27.4cm(W) x 36.8cm(H)	100/115V AC, 2.5A 60Hz (220-240V AC, 1.8A 50/60Hz CE)	8.8 lbs (3.97 kg)
LD6100	.25" to 4.75" (6mm to 121mm)	.50" to 6" (13mm to 152mm)	12" (31cm)	6.6"/sec* (16.8cm/sec.)	10.8"(L) x 10.8"(W) x 14.5"(H) 27.4cm(L) x 27.4cm(W) x 36.8cm(H)	100/115V AC, 2.5A 60Hz (220-240V AC, 2A 50Hz CE)	8.8 lbs (3.97 kg)

*Feed Speed calculated at take-up hub origin. Feed Speed will increase as material dispenses. Speed calculated at 60Hz.

Please refer to our website for the latest products and specifications. Specifications are subject to change without notice.
info@startinternational.com ▪ www.STARTinternational.com